


**MISSOURI PUBLIC SERVICE COMMISSION
MANUFACTURED HOUSING DEPARTMENT
APPROVAL OF ANCHORING SYSTEMS
STYLE CREST**

I.D. #	DESCRIPTION	SOIL TYPE	DUAL STRAP
30 DH	5/8" x 30" Double 4" Helix Auger Anchor	2, 3	NO
36 DH	5/8" or 3/4" x 36" Double 4" Helix Auger Anchor	2, 3	NO
48 DH	3/4" x 48" Double 4" Helix Auger Anchor	2, 3, 4	NO
40 SH	5/8" or 3/4" x 40" Single 6" Helix Auger Anchor	2, 3, 4	NO
48 SH	5/8" or 3/4" x 48" Single 6" Helix Auger Anchor	2, 3, 4,	NO
CDE8	5/8" x 13 3/4" Swivel Head Concrete Anchor	12" Thick, 2500 p.s.i Concrete @ 28 days	NO
DTH	Concrete Anchor with HN5830 Anchor Bolt	3760 p.s.i. Concrete @ 28 days	NO
SB 1/6	Zinc Plated Strap Buckle		
SB	Split Bolt		
FH6 (8 or 12)	Frame Hook w/6' x 8' or 12' of Galvanized Strap		
SB6 (8 or 12)	Zink Plated Strap Buckle w/6' or 8' or 12' Galvanized Strap		
24 DA	11/16" x 34" Cross Drive Rock Anchor	Rock	NO
S-100	1 1/4" x 0.35 Galvanized Anchor Strap		
57SH	3/4" x 60" Single 7" Helix Auger Anchor	4	
482201	9 1/8" x 20" Stabilizer Plate		
48233	*Tie Down Engineering Stabilizer Plate		

STANDARDS FOR INSTALLATION:

- 1) Anchors and all components must be installed per manufacturer's approved instructions.
- 2) Anchors are approved for designated soil type only.
- 3) One strap per anchor unless the anchor is approved for dual strap use.
- 4) Consult manufactured home set up instructions for number of tie downs, over the roof tie downs (if required), and tie down spacing.

DATE: August 23, 1996



JAMES PHILLIPS
DIRECTOR
MANUFACTURED HOUSING

The system being used on your home is _____

*Stylecrest stabilizer plate bearing part number 48233 is manufactured by Tie-Down Engineering (part number 59292).